

# Eaton FERRUPS Rackmount 60 Hz



Unmatched reliability in configurable power protection for computers and telecommunications equipment

## Features

- Active voltage regulation converts power from almost any AC source into computer grade power
- Eliminates harmful harmonic currents from entering a building's wiring, where they can disrupt computer operations
- Enhanced diagnostics initiate automatic startup and scheduled tests on the logic board, battery and other critical systems
- Provides regulated output voltage without drawing power from batteries, keeping the batteries fully charged for unexpected blackouts
- Complete offering of LanSafe® power management software included to ensure data integrity
- Enables automatic shutdown of UPS-protected devices with NetWatch Client 5.0 software
- Provides investment protection with a two-year limited warranty and \$250,000 load protection guarantee (U.S. and Canada)

## Product snapshot

<b>Rating:</b>	1.4 kVA–7 kVA
<b>Input voltage:</b>	120/208/240
<b>Output voltage:</b>	120/208/240
<b>Frequency:</b>	60 Hz
<b>Configuration:</b>	Rackmount

Eaton® FERRUPS® UPSs furnish unmatched reliability in configurable power protection for computers and telecommunications equipment. Patented ferroresonant technology delivers "bulletproof" power protection, overcoming spikes, sags, surges, noise and lightning. Eaton-exclusive SineSense provides clean, reliable power while conserving batteries during blackouts.

Extensive configurability options make FERRUPS the ideal power protection solution with a wide range of voltages, frequencies, runtimes, power cords and receptacles. FERRUPS prevents the backfeed of harmonic currents into building wiring, which can disrupt computer operations. Redundant power paths

assure high fault-tolerance and optimum uptime. Galvanic isolation separates input from output, filtering line noise and surges.

FERRUPS also features precision voltage regulation with no battery discharge down to 38% below nominal (depending upon load) as well as over 80 user-programmable diagnostic and communications functions.

FERRUPS models include free Eaton Software Suite power management software with connectivity cable and are BestLink SNMP/Web-ready for remote management. FERRUPS covers up to \$250,000 for damage to connected equipment resulting from a spike or surge (U.S. and Canada only).



Eaton NetWatch Client 5.0 has tested compatible with Cisco Unified Communications Manager 4.3. Go to [www.eaton.com/PQ/cisco](http://www.eaton.com/PQ/cisco) for disclaimer.



Powering Business Worldwide

# Technical specifications

Model		1.4 kVA	2.1 kVA	3.1 kVA	7 kVA*
Model No.		FES1.4 kVA	FER2.1 kVA	FER3.1 kVA	FER7 kVA
Capacity (kVA/kW)		1.4/1	2.1/1.5	3.1/2.2	7/5
Dimensions H x W x D	inches mm	9.75 x 16 x 21.25 248 x 406 x 540	9.75 x 16 x 26.25 248 x 406 x 667	9.75 x 16 x 26.25 248 x 406 x 667	19 x 16 x 26.25 483 x 406 x 667
Front panel H x W	inches mm	10.5 x 19 267 x 483	10.5 x 19 267 x 483	10.5 x 19 267 x 483	19.25 x 19 489 x 483
Battery pack H x W x D	inches mm	Internal	Internal	Internal	8.3 x 16.25 x 24.25 211 x 413 x 616
Weight (includes batteries)	lb kg	150 68	220 100	238 108	580 263
Input—hardwired connection circuit breaker requirement (contact factory for powercord options)		120=15A 208=10A 240=10A	120=25A 208=15A 240=15A	120=35A 208=20A 240=15A	120=65A 208=40A 240=35A
Output connection		Hardwired output is standard. Contact factory for receptacle options.			
Typical runtime: (minutes)	full load half load	14 36	24 58	14 35	12 33

## Operation

Nominal input voltage		120/208/240			
Input voltage range		+15%, -20%			
Operating frequency		60 Hz (online: $\pm 0.01$ Hz to $\pm 3$ Hz adjustable, on inverter: $\pm 0.005$ Hz)			
Nominal output voltage		120/208/240			
Output voltage regulation		$\pm 3\%$ for input voltages +15%, -20% of nominal. +5%, -8.3% for any line, load or battery condition			
Output voltage waveform		Sine Wave			
Output voltage		THD 5% or less THD at rated kW load			
Overload capacity		150% surge and 125% for 10 minutes on-line. 150% surge and 110% for 10 minutes on inverter			
Transfer time		0 ms			
Lightning, surge and noise protection		2000: 1 spike attenuation using C62.41 and C62.45 Category A and Category B tests Noise rejection: common mode—>120 dB, normal mode—>60 dB			
Efficiency % (online)		88	90	91	90
Heat (online)	BTU/hr kW/hr	465 0.136	568 0.166	742 0.217	1896 0.556
Battery charger (DC)		12V, 4A	48V, 4A	48V, 4A	48V, 5A
Safety certification		UL, CSA (CUL)			
EMI compliance		FCC Class A			
Testing standards		ANSI/IEEE C62.41 (1980); ANSI/IEEE C62.45 (1987); IEC 801-2, 801-4, 801-5			
Communication		DB25 communication port with RS-232 serial communications, alarm and inverter contact closures, and EPO shutdown.			

## Environmental

Operating temperature		0° to 40°C			
Storage temperature		-20° to +60°C (-20° to +40°C if battery not removed)			
Relative humidity		5 to 95% without condensation			
Audible noise (dBA)		50	50	51	52
Altitude		3050m (10,000 ft) maximum			

\* 7 kVA model includes front panel keypad and display. All specifications typical and are subject to change without notice.



UNITED STATES  
8609 Six Forks Road  
Raleigh, NC 27615 U.S.A.  
Toll Free: 1.800.356.5794

[www.eaton.com/powerquality](http://www.eaton.com/powerquality)

CANADA  
Ontario: 416.798.0112  
Toll free: 1.800.461.9166

LATIN AMERICA  
Brazil: 55.11.3616.8500  
Caribbean: 1.949.452.9610  
México & Central America:  
52.55.9000.5252  
South Cone: 54.11.4343.6323

EUROPE/MIDDLE EAST/AFRICA  
Denmark: 45.3686.7910  
Finland: 358.94.52.661  
France: 33.1.6012.7400  
Germany: 49.0.7841.604.0  
Italy: 39.02.66.04.05.40  
Norway: 47.23.03.65.50  
Sweden: 46.8.598.940.00  
United Kingdom: 44.1753.608.700

ASIA PACIFIC  
Australia: 61.2.9693.9366  
New Zealand: 64.0.3.343.3314  
China: 86.21.6361.5599  
HK/Korea/Taiwan: 852.2745.6682  
India: 91.11.4223.2300  
Singapore/SEA: 65.6825.1668

Eaton, LanSafe, Powerware, PowerChain Management and FERRUPS are trade names, trademarks and/or service marks of Eaton Corporation or its subsidiaries and affiliates. All other trademarks are property of their respective owners.