

EATON

Powerware

Powerware® 9355 Uninterruptible Power System

Stand-alone UPS solutions up to 40 kVA
Hot Sync® UPS parallel systems with redundancy/capacity



Features

- Patented Hot Sync® redundancy and modular upgrades up to 4 x parallel systems
- Advanced Battery Management (ABM™), significantly extends battery service life compared to traditional charging method
- Active input power factor correction (PFC) providing unbeatable 0.99 input power factor and 2-5% THD(i) harmonics
- Optimised 0.9 p.f. output rating for server and computer loads
- Market leading internal battery runtime
- User friendly multilingual LCD display with settings, meters and active mimic capability
- Web/SNMP, Modbus/JBus and Industrial Relays monitoring capability

Powerware 9355, a Series 9 UPS, is designed to protect high 0.9 p.f. rated, critical computers and servers. The centralised UPS protection is an essential part of IT infrastructure in today's IT, telecom, healthcare, banking and industrial automation applications. The Powerware 9355 features high 93% efficiency, active input power factor control (PFC) and low 2-5% THD(i) with the modern IGBT rectifier technology.

With the Hot Sync® technology it is possible to parallel one or more UPS units to increase availability. The patented Hot Sync technology enables load sharing without any communication line, thus eliminating the single point of failure.

The Powerware 9355 operates using the unique Advanced Battery Management (ABM™) function. While traditional UPS charges batteries continuously, ABM charges

batteries only when necessary, thus preventing battery corrosion. This exceptional ABM function significantly prolongs the service life of batteries.

A novel small footprint and long runtimes with internal batteries Powerware 9355 saves valuable space in the data centers and computer rooms. Together with a wide range of models and options ensures the double conversion online Powerware 9355, with three phase output, is the ideal UPS for critical power protection applications.

Bundled with the Powerware Software Suite, the Powerware 9355 protects all network devices and has the additional advantage of providing an orderly network shutdown in event of an extended power outage. If required, the Powerware 9355 can also be integrated to any network management (Web/SNMP) and building management (ModBus/Jbus) system.

Technical Specifications

POWERWARE 9355

General

Output rating	20-40 kVA 0.9 p.f.
Efficiency	93% at nominal load
Audible noise	<50 dB (A)

Input

Nominal voltage	400 V (3-phase input/output)
Frequency	45-65 Hz
Power factor	0.99 (2-5% THDi at nominal load)

Output

Selectable voltage	380/400/415 VAC; 50 or 60 Hz
Regulation	±2% static
Power factor	0.9 (e.g. 27 kW at 30 kVA)
Permitted load power factors	0.7 lagging - 0.8 leading
Overload	150% for 1 min, 125% for 10 min, 110% for 60 min (mains available)

Battery

Type	Maintenance free VRLA batteries
Battery charging	Advanced Battery Management (ABM™)
Battery nominal voltage	432 V (36 x12 V, 216 cells)
Battery max. voltage	507 V (2.35 VPC)
Battery min. voltage	378 V (1.75 / 1.67 VPC)

Options

Isolation transformer,
Long-life 10y battery options,
External battery cabinets,
XSlot connectivity (Web/SNMP, ModBus/JBus,
Relay, Hot Sync),
Parallel tie cabinets

Markings

Approvals	CE, GOST
Quality	ISO9001:2000 & ISO14001:2004

Standard UPS with 3-phase input

Part no	Description	Rating	Runtime (pf 0.7)	Dimensions (HxWxD)	Weight
1025061	PW9355-20i-N-5; MBS	20 kVA / 18 kW	5 min	1684x494x762 mm	300 kg
1025062	PW9355-20i-N-13; MBS	20 kVA / 18 kW	13 min	1684x494x762 mm	400 kg
1025063	PW9355-20i-N-22; MBS	20 kVA / 18 kW	22 min	1684x494x762 mm	500 kg
1025064	PW9355-20i-N-31; MBS	20 kVA / 18 kW	31 min	1684x494x762 mm	600 kg
1025065	PW9355-30i-N-7; MBS	30 kVA / 27 kW	7 min	1684x494x762 mm	400 kg
1025066	PW9355-30i-N-13; MBS	30 kVA / 27 kW	12 min	1684x494x762 mm	500 kg
1025067	PW9355-30i-N-20; MBS	30 kVA / 27 kW	20 min	1684x494x762 mm	600 kg
1025089	PW9355-20i-N-0; MBS	20 kVA / 18 kW	0 min	1684x494x762 mm	200 kg
1025090	PW9355-30i-N-0; MBS	30 kVA / 27 kW	0 min	1684x494x762 mm	200 kg
1025795	PW9355-40i-N-8; MBS	40 kVA / 36 kW	8 min	1684x494x762 mm	517 kg
1025796	PW9355-40i-N-12; MBS	40 kVA / 36 kW	12 min	1684x494x762 mm	617 kg
1025803	PW9355-40i-N-0	40 kVA / 36 kW	0 min	1684x494x762 mm	317 kg
1025804	PW9355-40i-N-0; MBS	40 kVA / 36 kW	0 min	1684x494x762 mm	317 kg

External battery cabinets

Part no	Description	Rating	Runtime	Dimensions (HxWxD)	Weight
1025169	PW9355-BAT5 (36x24Ah)	1x36x24 Ah	See runtime spec	1684x494x758 mm	510 kg
1025170	PW9355-BAT5 (72x24Ah)	2x36x24 Ah	See runtime spec	1684x494x758 mm	870 kg
1025168	PW9355-BAT (1x36 blks)	-	-	1684x494x758 mm	150 kg
1025667	PW9355-20/30 Batt Kit Assy	-	-	-	-

In the interest of continual product improvement all specifications are subject to change without notice.

Powerware®, Advanced Battery Management, LanSafe, PowerVision, and FORESEER are trademark(s) of Eaton Power Quality Corporation. © 2004 Eaton Corporation

Mailing Address:
Eaton Power Quality Pte Ltd
15 Changi Business Park Central 1
Level 3 Singapore 486057
Tel: +65 6825 1684
Fax: +65 6825 1689
EatonSEA@eaton.com
www.eaton.com/powerware

INDONESIA
Tel: +6221 522 6181
Fax: +6221 522 6182

MALAYSIA
Tel: +603 7804 3618
Fax: +603 7803 6193

THAILAND
Tel: +662 946 6843
Fax: +662 519 0574

VIETNAM
Tel: +844 936 5303
Fax: +844 936 5307

For more product information, please contact:



Powerware