

# EAT•N

# Powerware

## Powerware DSFi Single Phase High Performance Surge Filter

Product Focus

Series Filter with Shunt surge diverter,  
1 Phase 5-32A, 50kA Primary



The DSFi is designed to provide secondary protection against power surges caused by external sources such as lightning strikes and substation switching as well as providing a measure of protection from surge events generated on the secondary side of the filter. An ideal device for Category B locations.

The DSFi is a 3-stage protection unit utilising primary and secondary MOV protection in conjunction with a 2-stage Low-Q LC filter (i.e. 2 inductive coils) using separate differential mode and common mode circuits. The unit provides filtering of the line harmonics, noise and RF transmitters with a cut-off frequency of <math><1.5\text{kHz}</math> and a minimum attenuation of >55dB to 10MHz.

Secondary MOV protection (in all 3 modes) is located after the inductive coils, to provide further surge reduction and to protect against load-generated surges.

### Features

- Surge suppression and filtering in a single package
- 2 mode, 5 Element Series Filter
- 3 mode, 2 Stage Surge Diverter
- Modular design
- Enclosed in IP20 painted steel housing
- Protection Fail Alarm Relay
- 5 Year Warranty

### Typical applications:

- Secondary power circuits/Sub-boards
- UPS Systems and Rectifiers
- Telecommunications Systems and Rectifiers
- Process and Control Systems and UPS's up to 6kVA
- Computer Systems and Medical Systems
- AV circuits for clubs and hotels
- All sensitive Electronic Equipment



# Technical Specifications

## POWERWARE DSFi

Technical Specification	DSFi
Input voltage	200-250VAC 1 Phase
Maximum continuous voltage - MCOV	300VAC
Temporary overvoltage - TOV	320VAC, 15 mins
Service type	TT, TN, TN C-S or any single-phase system with a grounded neutral.
Energy Absorption rating - per mode (Joules)	Primary Protection L-N = 740 J Primary common mode protection L-E & N-E = 780 J Secondary protection L-N = 225J Secondary common mode protection L-E & N-E = 480J Aggregate rating = 2,225J
Current rating – continuous	5 - 32A
Recommended max. overcurrent protection	32A (C curve MCCB)
Short circuit withstand (1 sec)	Suitable for use with a 6kAIC C Curve MCB
Protection modes	Line-Neutral, Line-Earth, Neutral-Earth
In 8/20us (Line-Neutral)	15kA x 20 hits
In 8/20us (Line-Earth)	10kA x 20 hits
In 8/20us (Neutral-Earth)	10kA x 20 hits
I <sub>max</sub> 8/20us (Line-Neutral)	50kA
I <sub>max</sub> 8/20us (Line-Earth)	25kA
I <sub>max</sub> 8/20us (Neutral-Earth)	25kA
Residual voltage (V <sub>pl</sub> ) (Line-Neutral). (Let through voltage)	<1100 (3kA, 8/20uS)
Residual voltage (V <sub>pl</sub> ) (Line-Earth). (Let through voltage)	<1400 (3kA, 8/20uS)
Residual voltage (V <sub>pl</sub> ) (Neutral-Earth). (Let through voltage)	<1400 (3kA, 8/20uS)
Filter attenuation	> 55dB to 10MHz
Initial clamp voltage (Line-Neutral)	560V (350Vac RMS)
Initial clamp voltage (Line-Earth)	680V (420Vac RMS)
Initial clamp voltage (Neutral-Earth)	680V (420Vac RMS)
Internal protection (fusing)	Thermal
Terminations	10mm <sup>2</sup> PCB Mounted Terminals
Alarms/indicators	2 LED display, Power OK & Protection OK LEDs, Dry contact alarm relay output – 250Vac/32Vdc, 5A, 5kV isolation, Alarm under-voltage cutoff 180Vac
Enclosure rating	IP20
Design Standards:	IEC61643-1, IEC610006-1,2,3,4 ANSI/IEEE C62.41 Cat B,C,D,E AS1768-1991 Cat B,C,D,E AS3000,AS3100, CE mark
Dimensions & Weight	140 x 50 x 270 mm (W x D x H), 1.5kg
Environment	-10 to 65 C, 10 to 90%RH (non-condensing)

In the interests of continual product improvement all specifications are subject to change without notice.

Eaton, Powerware, Hot Sync, Advanced Battery Management, LanSafe, PowerVision, and FORESEER are trade names, trademarks, and/or service marks of Eaton Corporation or its subsidiaries and affiliates. © 2007 Eaton Corporation, All Rights Reserved.

### HEAD OFFICE

Eaton Power Quality Pty Ltd  
10 Kent Road  
Mascot NSW 2020  
Phone: +61 2 9693 9366  
Fax: +61 2 8338 1159  
www.powerware.com.au

### SALES OFFICES

Queensland  
Phone: +61 7 3844 9728  
Fax: +61 7 3217 2199

Victoria  
Phone: + 61 3 9706 5662  
Fax: + 61 3 9794 9150

SOUTH AUSTRALIA  
Phone: +61 8 8347 3622  
Fax: +61 8 8445 6328

Western Australia  
Phone: +61 8 9446 0520  
Fax: + 61 8 9244 7466

Auckland New Zealand  
Phone: + 64 9 273 3970  
Fax: +64 9 273 3980

WELLINGTON New Zealand  
Phone: + 64 4 477 4717  
Fax: +64 4 477 3691

Sales 1300 UPS UPS

Service 1300 303 059

